



REV	DESCRIPTION	DRAWN BY	CHKR	APVD	APVD	D R
1	ADD SPLICE BAR, MOVED LIFT RING	SDM				04-04
2	REMOVED 3.6 DIM	RHC				11/05
3	ADDED DIMENSION	TP				7/10

DIMENSIONAL TOLERANCES APPLY UNLESS OTHERWISE SPECIFIED	
DIMENSIONAL TOLERANCES—INCHES(1)	DIMENSIONAL TOLERANCES MILLIMETERS
1 DECIMAL PLACE ±.06	0 DECIMAL PLACES ±1.5
2 DECIMAL PLACES ±.02	1 DECIMAL PLACE ±.5
3 DECIMAL PLACES ±.005	2 DECIMAL PLACES ±.12
ANGULAR DIMENSIONS ±0°30'	
1. REF: ANSI STD Y14.5	
2. POSITIONAL TOLERANCES AND RELATED DATUMS APPLY AT MMC	
3. MMC—MAXIMUM MATERIAL CONDITION	
4. RFS—REGARDLESS OF FEATURE SIZE	
5. PERFECT FORM REQUIRED AT MMC	
TOLERANCES OF FORM AND POSITION (1) (2) (5)	
FLATNESS	IRREGULARITY
STRAIGHTNESS	ANGULARITY
CIRCULARITY	CIRCULAR RUNOUT
CYLINDRICITY	POSITION
PROFILE OF ANY LINE	CONCENTRICITY/COAXIALITY
PROFILE OF ANY SURFACE	SYMMETRY
PARALLELISM	FEATURE CONTROL SYMBOL (ANSI/ISO 1151)

MEMBRANA  
MEMBRANA  
Underlining Performance

RFA NO		CA NO		DO NOT SCALE THIS DRAWING	
DRAWN BY: SDM		12-03-03		THIRD ANGLE PROJECTION	
CHECKED BY:		APPROVED FOR CONSTRUCTION		SHEET NO: 1 OF 1	
APPROVED BY:		SUPERSEDES:		SCALE: NONE	
APPROVED BY:		SUPERSEDED BY:		DRAWING NUMBER: SMC-0114-12-6437	
REVISION: 3		DRAWING NUMBER: SMC-0114-12-6437		REVISION: 3	
DRAWING TITLE: 14 X 28 CONTACTOR MOUNTING STRAP ASSEMBLY		PLAN FILE NO:		POCKET NO:	

REF MACHINE